



# SEANEXX

Developed in Austria for FT-TEC USA Corp.

Foto: © Fotolia.de, Gestaltung: www.EDUMESS-Webshop.at

# SEANEXX

## SEANEXX SETS – The basic receiver station from a single source!



### SEANEXX RX110-UHF/BNC

2-channel receiver equipped **with GPS indicating one's own position**  
Available with magnetic base or clip antenna

### SEANEXX RX200-UHF/BNC

2-channel receiver for **simultaneous reception of both AIS channels**  
Available with magnetic base or clip antenna

### SEANEXX RX210-UHF/BNC

2-channel receiver for **simultaneous reception of both AIS channels** equipped  
**with GPS indicating one's own position** Available with magnetic base or clip antenna



# AIS RECEIVER

Only those who keep an overview are safe on board

[www.seanexx.com](http://www.seanexx.com)

FT-TEC USA Corp., 2272 Airport RD S, Suite 201, Naples, FL 34112  
Telephone: +1 (773) 543 9893, [www.ft-tec.com](http://www.ft-tec.com)

Developed in Austria for FT-TEC USA Corp.

# Simply AIS

With the SEANEXX AIS USB STICK, you can receive all your yacht's AIS signals in a compact, practical and easy way. Thus, you always keep an overview of boats or emergency signals in your vicinity.

SEANEXX RX110-UHF/BNC – 2-channel receiver equipped with GPS indicating one's own position

SEANEXX RX200-UHF/BNC – for simultaneous reception of both AIS channels

SEANEXX RX210-UHF/BNC – for simultaneous reception of both AIS channels equipped with GPS indicating one's own position

Only those who keep an overview are safe on board!

[www.seanexx.com](http://www.seanexx.com)

## This is how it works:

- 1 Download SEANEXX Connect
- 2 Connect SEANEXX to your pc's or laptop's USB port
- 3 Open the map software (e.g. OpenCPN)
- 4 Mount antenna
- 5 Receive AIS!

## Technical Details

Model	RX110	RX200	RX210
AIS receiver	Alternating AIS 1 (161.975 MHz) AIS 2 (162.025 MHz)	2-channel receiver AIS 1 (161.975 MHz) AIS 2 (162.025 MHz)	2-channel receiver AIS 1 (161.975 MHz) AIS 2 (162.025 MHz)
GPS receiver	GNSS module (GPS, Glonass, Beidou)	-	GNSS module (GPS, Glonass, Beidou)
Outlet	USB		
Power supply	directly via USB interface		
Storage/operating temperatures	-22°F to 167°F		
Dimensions	2.54 x 0.80 x 4.25 inch		
Humidity	20% to 85% relative humidity		
Accessories	<ul style="list-style-type: none"> <li>● Included: Adapter cable for BNC and PL239</li> <li>● Clip-mount antenna (optional)</li> <li>● Magnetic base antenna (optional)</li> <li>● Antenna splitter/antenna combiner (optional)</li> <li>● AIS receipt via up to 10 smart phones/tablets/laptops simultaneously as "MOBILE AIS" package (optional)</li> </ul>		



**SEANEXX**

Developed in Austria for FT-TEC USA Corp.

Magnetic base antenna

Compatible with AIS-ready navigation software (e.g. OpenCPN)